



INGO MAURER

Satel.light

Ingo Maurer und Team 2005

Fiberglass, Metall, Aluminium. 230/125/12 Volt. 230 Volt: 100 Watt. 125 Volt: 50 Watt. Halogen. Sockel GY6,35. Stufenlos dimmbar. Stab um 350° drehbar. Arm mit Reflektorschale um ca. 90° schwenkbar. Lieferung mit Leuchtmittel.

Fibreglass, metal, aluminium. 230/125/12 volts. 230 volts: 100 watts. 125 volts: 50 watts. Halogen. Socket GY6,35. Continuously variable dimmer. Stem rotates through 350°, arm with reflector dish tilts through approx. 90°. Complete with bulb.

Vetroresina, metallo, alluminio. 230/125/12 volt. 230 watt: 100 watt. 125 volt: 50 watt. Alogena. Attacco GY6,35. Regolazione continua dell'intensità luminosa. Asta rotante di 350°, braccio con riflettore basculante di ca. 90°. Lampadina inclusa.

Fibre de verre, métal, aluminium. 230/125/12 volts. 230 volts: 100 watts. 125 volts: 50 watts. Halogène. Culot GY6,35. Réglage de l'intensité lumineuse sans graduation. Tige rotative à 350°, bras avec antenne orientable à 90°. Livrée avec ampoule.

